



IELECOMMUNICATIONS

Friction Coefficient Testing for Rooftop Ballast Mounts

Testing completed by: Perfect Vision and Sabre Industries

NOTICE OF DISCLAIMER AND LIMITATIONS OF LIABILITY

THE TELECOMMUNICATIONS INDUSTRY FOUNDATION ("TIF") DOES NOT ENFORCE OR MONITOR COMPLIANCE WITH THE CONTENTS OF THIS DOCUMENT. ADDITIONALLY, TIF DOES NOT CERTIFY, INSPECT, TEST, OR OTHERWISE INVESTIGATE PRODUCTS, DESIGNS, OR SERVICES OR ANY CLAIMS OF COMPLIANCE WITH THE CONTENTS OF THIS DOCUMENT.

ALL WARRANTIES, EXPRESS OR IMPLIED, ARE DISCLAIMED, INCLUDING WITHOUT LIMITATION, ANY AND ALL WARRANTIES CONCERNING THE ACCURACY OF THIS DOCUMENT OR ITS CONTENTS, ITS FITNESS OR APPROPRIATENESS FOR A PARTICULAR PURPOSE OR USE, ITS MERCHANTABILITY, AND ITS NONINFRINGEMENT OF ANY THIRD PARTY'S INTELLECTUAL PROPERTY RIGHTS. TIF EXPRESSLY DISCLAIMS ANY AND ALL RESPONSIBILITIES FOR THE ACCURACY OF THE CONTENTS HEREIN AND MAKES NO REPRESENTATIONS OR WARRANTIES REGARDING THE CONTENT'S COMPLIANCE WITH ANY APPLICABLE STATUTE, RULE, REGULATION, INDUSTRY STANDARD, OR THE SAFETY OR HEALTH EFFECTS OF THE CONTENTS HEREOF OR ANY PRODUCT OR SERVICE REFERRED TO IN THIS DOCUMENT OR PRODUCED OR RENDERED TO COMPLY HEREWITH.

TIF SHALL NOT BE LIABLE FOR ANY DAMAGES, DIRECT OR INDIRECT, ARISING FROM OR RELATING TO ANY USE OF THIS DOCUMENT OR THE CONTENTS CONTAINED HEREIN, INCLUDING WITHOUT LIMITATION, ANY AND ALL INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES (INCLUDING DAMAGES FOR LOSS OF BUSINESS, LOSS OF PROFITS, LITIGATION, OR THE LIKE), WHETHER BASED UPON BREACH OF CONTRACT, BREACH OF WARRANTY, TORT (INCLUDING NEGLIGENCE), PRODUCT LIABILITY, OR OTHERWISE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING NEGATION OF DAMAGES IS A FUNDAMENTAL ELEMENT OF THE USE OF THE CONTENTS HEREOF, AND THESE CONTENTS WOULD NOT BE PUBLISHED OR SPONSORED BY THE TELECOMMUNICATIONS INDUSTRY ASSOCIATION ("TIA") OR TIF WITHOUT SUCH LIMITATIONS. THE DOCUMENT IS TO BE USED FOR INFORMATION PURPOSES ONLY AND IS INTENDED TO PROVIDE AN OVERVIEW FOR EDUCATIONAL PURPOSES AND TO SOLICIT INPUT FROM THE TELECOMMUNICATIONS INDUSTRY.

THIS DOCUMENT IS NOT A STANDARD. THIS DOCUMENT ONLY REPRESENTS THE COMMENTS AND OPINIONS OF THE AUTHORS AND IS NOT INTENDED TO SUPERSEDE, MODIFY, OR INTERPRET ANY STATUTE, RULE, REGULATION, OR OTHER INDUSTRY OR TIA STANDARD. THE PUBLICATION OF THIS DOCUMENT DOES NOT REPRESENT THE POSITION OR ENDORSEMENT OF TIA OR TIF.

ANTITRUST STATEMENT

THE TELECOMMUNICATIONS INDUSTRY FOUNDATION ("TIF") SUPPORTS FULL COMPLIANCE WITH ANTITRUST AND COMPETITION LAWS. ALL INDIVIDUALS WHO ASSISTED IN THE DEVELOPMENT OF THIS TIF DOCUMENT AND ANY PARTICIPANTS IN MEETING CONVENED, ORGANIZED, OR SUPPORTED BY TIF, INCLUDING BUT NOT LIMITED TO, THE PARTICIPANTS, TIF BOARD OF DIRECTORS, OFFICERS, AND EMPLOYEES, TIF COMMITTEE MEMBERS, AND OTHER INVITED GUESTS (TOGETHER, THE "ATTENDEES") ARE EXPECTED TO TAKE ALL REASONABLE MEASURES NECESSARY TO COMPLY WITH APPLICABLE STATE AND FEDERAL ANTITRUST AND COMPETITION LAWS.

ATTENDEES SHOULD NOT DISCUSS OR EXCHANGE INFORMATION OR DATA CONCERNING PRICING, TERMS AND CONDITIONS OF SALE AFFECTING PRICE, INDUSTRY PRICING POLICIES, MARKETING PROCEDURES, ALLOCATIONS OF FUNDS, CUSTOMER LISTS, RESTRICTIONS ON TYPES AND QUANTITY OF PRODUCTS AND SERVICES, REFUSALS TO DO BUSINESS WITH CERTAIN SUPPLIERS OR CUSTOMERS, OR OTHER SIMILAR TOPICS. FURTHER INFORMATION CONCERNING TIF'S ANTITRUST POLICY IS AVAILABLE UPON REQUEST

Participation



- Testing occurred at Manufacturer locations
- Roofing material samples supplied by Nohava Construction and Congruex (True North)









Materials Utilized in Testing

- Four (4) typical roof membranes:
 - TPO
 - PVC
 - EPDM
 - Asphalt



• Two (2) different types of typical rubber mats that are recommended to be used under rooftop ballast mounts:



- Galvanized steel parts:
 - 3.5" diameter x 1/4" thick plate
 - 1.75" OD x 1/8" thick washer

© TELECOMMUNICATIONS INDUSTRY FOUNDATION. THIS DOCUMENT IS TO BE USED FOR EDUCATIONAL PURPOSES ONLY, AND IS INTENDED TO GENERATE DISCUSSION

Method of Testing


• Ten (10) Test Configurations using Two (2) Different Rubber Mats, Four (4) Different Roofing Membranes plus Galvanized Steel.

Test Configuration	Material 1	Material 2	Test Configuration	Material 1	Material 2
1	Rubber Mat 1	TPO	6	Rubber Mat 2	ТРО
2	Rubber Mat 1	PVC	7	Rubber Mat 2	PVC
3	Rubber Mat 1	EPDM	8	Rubber Mat 2	EPDM
4	Rubber Mat 1	Asphalt	9	Rubber Mat 2	Asphalt
5	Rubber Mat 1	Galvanized Steel	10	Rubber Mat 2	Galvanized Steel

• Testing committee had multiple meetings to discuss materials and then selected these configurations to represent most common scenarios.


• Rubber mats from different manufacturers used for representative purposes, consistency and validation.


Method of Testing




Solving for $\sum F_{\parallel}$ and $\sum F_{\perp}$ $\mu_s = \tan \theta$

- Minimum of three (3) tests for each configuration.
- Eight (8) tests for at least one configuration to test directionality Two (2) tests for each sample orientation 0, 90, 180, and 270 degrees.
- Angle when observable movement (~1/8") occurred was recorded for each test.
- Angles used to calculate friction coefficient.
- Testing occurred at three (3) separate locations by qualified personnel.
- Test results aggregated by third party.













- Some material combinations had a gradual slip and others had more of an immediate slip at the recorded angle.
- Averages are recommended values to use for analysis or design purposes.
- Galvanized steel results reported are for newly galvanized, not weathered parts.
 - Limited testing on weathered galvanized steel parts yielded higher values.

TIF summary of friction coefficient testing						
Material 1	Material 2	Number of Tests	Average Coefficient			
Rubber Mat	TPO Membrane	38	0.72			
Rubber Mat	PVC Membrane	28	0.75			
Rubber Mat	EPDM Membrane	28	0.76			
Rubber Mat	Asphalt Membrane	28	1.02			
Rubber Mat	Galvanized Steel	36	0.63			

TIF recommended friction coefficients						
Material 1	Material 2	Number of Tests	Average Coefficient			
Rubber Mat	TPO/PVC/EPDM Membrane	94	0.74			
Rubber Mat	Asphalt Membrane	28	1.02			
Rubber Mat	Galvanized Steel	36	0.63			



Thank You

The Telecommunications Industry Foundation would once again like to thank the following participants who supported their respective employee's participation in this testing event. The participants took time out of their busy schedules to work in conjunction with competitors in order to move our industry forward. The observations and empirical data gathered from this event will serve to educate many.

Perfect Vision

Sabre

TES / Congruex

Colliers